



FLUIDE G3

Automatic transmission lubricant dedicated to hydraulic systems and power steering application

PERFORMANCES LEVELS

OEM-Approved	Meets the requirements	Suitable for
✓ Mercedes MB-Approval 236.9	✓ GM Dexron IIIG / IIIH	✓ Allison C4
✓ Volvo 97341	✓ Ford Mercon	
✓ MAN 339 Typ V1/Z1/L1		
✓ Voith H55.6335.xx		
✓ ZF TE-ML 04D/14A/11B		

APPLICATIONS

- Particularly adapted to heavy duty and passengers car application
- Recommended for all automatic transmissions and hydraulic systems when the manufacturer requires an Automatic Transmission Fluid (ATF) GM DEXRON®III.

CUSTOMER BENEFITS

- **Outstanding thermal stability** in operation thanks to its high antioxidant and detergent level
- **Excellent friction properties** giving controlled slip for friction components: gear shifting quality, demands smooth clutching action without excessive slip.
- This lubricant enables **precise and smooth automatic shifting** even at very low speed.

TOTAL LUBRIFIANTS – Immeuble Spazio
562, avenue du Parc de l'île
92029 Nanterre cedex
France

FLUIDE G3
Update: 07/2017



This lubricant does not cause adverse health effects when used in the intended application. A safety datasheet, is accessible on request from your local dealer.

- ELFMATIC G3 has a **low temperature fluidity** to avoid surge or sudden overload of circuits when starting in very cold weather.
- This lubricant provides **high antiwear, anticorrosion and antifoam performances**

PHYSICAL AND CHEMICAL CHARACTERISTICS

FLUIDE G3	Unit	Method	Value
Colour	-	ASTM D1500	Red
Density at 15°C	kg/m ³	ASTM D4052	843,5
Kinematic Viscosity at 40 °C	mm ² /s	ASTM D445	34,95
Kinematic Viscosity at 100°C	mm ² /s	ASTM D445	7,373
Brookfield Viscosity at -40°C	cP	ASTM D2983	9828
Viscosity Index	-	ASTM D2270	186
Pour Point	°C	ASTM D97	-45
Flash Point	°C	ASTM D92	198

**The features mentioned above are average values obtained with some variability in production and do not constitute a specification.*

RECOMMENDATIONS FOR USE

Before using the product, it is important to check the service manual of the vehicle: the drain is carried out according to the manufacturer's requirements.

The product should not be stored at a temperature above 60 °C while avoiding exposure to strong sunlight, extreme cold or high temperature variations.

All packages should be protected from bad weather conditions. Otherwise, the drums should be stored horizontally to avoid a possible contamination by water and the damage of the product label.

HEALTH, SAFETY AND ENVIRONMENT

Based on available information, this product does not cause adverse health effects when used in the intended application and the recommendations provided in the Safety Data Sheet (MSDS) are followed. The information is accessible on request from your local dealer or on the website www.quickfds.com.

This product should not be used for applications other than those for which it is intended.

If disposing of used product, take care to protect the environment and comply with local regulations.

TOTAL LUBRIFIANTS – Immeuble Spazio
562, avenue du Parc de l'île
92029 Nanterre cedex
France

FLUIDE G3
Update: 07/2017



This lubricant does not cause adverse health effects when used in the intended application. A safety datasheet, is accessible on request from your local dealer.

