

# 6-in-1 Spray



Aerosol



Multipurpose penetrating, cleaning and lubricating fluid

## APPLICATIONS

- Anti-seize/releasing oil, anti-oxidant, anti-corrosion, with good lubricating power
- Also cleans oil/grease/inorganic residues, removes bitumens
- For all kinds of rusted/seized mechanisms : hinges, pivots, rails, bolts, hardware...
- Can be used as a cleaner for chains, bearings, slides...
- *Shake the aerosol before use – Spray from a 10-15 cm distance*

## ADVANTAGES

- High penetrating power
- Non-flammable propellant gas : CO<sub>2</sub>
- Can be used upside-down for an easier manipulation of the spray
- Compatible with all plastics, elastomers and paints.

TYPICAL CHARACTERISTICS	METHODS	UNITS	6-in-1 Spray
Color	Visual	-	Colorless to yellow
Density at 15 °C	ISO 12185	kg/m <sup>3</sup>	800
Kinematic viscosity at 40 °C	ISO 3104	mm <sup>2</sup> /s	1.4
KB Index	ASTM D 1133	-	97
Flash Point (closed-cup)	ISO 2719	°C	62
Copper strip test	ISO 2160	-	1a
SRV Friction test	ASTM D 5707	-	0,09

Above characteristics are mean values given as an information.

## CAUTION

Due to the container and the presence of solvents :

- Keep away from heat, sparks and flames.
- Do not expose to heat and temperatures exceeding 50°C.
- Even when empty, do not puncture or incinerate the container.



TOTAL LUBRIFIANTS  
INDUSTRY  
01-11-2020  
6-IN-1 SPRAY



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.  
A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded from <https://sdstotalms.total.com>