

AERO DM 20W-60



Aviation



Ashless multigrade dispersive oil for aircraft piston engines.

APPLICATIONS

- Lubrication of piston engines operating under severe and **very severe conditions. Can be used throughout the year in any climate.**

SPECIFICATIONS

AERO DM 20W-60 meets the following specifications and technical instructions:

- SAE J-1899
- LYCOMING SI 1014M, SI 1409C, SB 446E, SB 471B
- FAA AD 08-04-03.

ADVANTAGES

- **TOTAL AERO DM 20W-60** is formulated with **high quality** base stocks. This provides very **high viscosity index**.
- The new formulation, made with the latest technologies specific additives, provides the best **antiwear** requirements for this type of oil.
- Its excellent dispersing performance guarantees an **outstanding engine cleanliness**.
- Its **very low pour point** and the multigrade properties allow for immediate lubrication at **low and very low temperatures**.
- It also provides **excellent oxidation and corrosion resistance**.
- **TOTAL AERO DM 20W-60** already contains, in the correct proportions, an anti-wear additive, the same as **TEXTRON Lycoming** additive LW 16702: by using **TOTAL AERO DM 20W-60**, it is not necessary to add this additive in the oil.

TYPICAL CHARACTERISTICS	METHODS	UNITS	AERO DM 20W-60
Specific gravity at 15 °C	ISO 3675	kg/m ³	871
Viscosity at 40 °C	ISO 3104	mm ² /s	185
Viscosity at 100 °C	ISO 3104	mm ² /s	24.3
Viscosity index	ISO 2909		163
Cleveland flash point	ISO 2952	°C	252
Pour point	ISO 3016	°C	- 36

Above characteristics are mean values given as an information.

**TOTAL LUBRIFIANTS
INDUSTRIE**

29-04-2016 (supersedes 25-05-2009)

AERO DM 20W-60

1/1



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.
A material safety data sheet conforming to the regulations in use in the E.C. is obtainable via your commercial adviser www.quick-fds.com.