



DYNATRANS ACX

10W – 30 – 50



Lubricant for **hydraulic systems** and **transmission components** (axles or gearboxes) equipped with specific **brake friction discs**

SPECIFICATIONS AND APPROVALS

API GL-4

Manufacturers' approvals

- ✓ ZF TE ML 03 C (SAE 10W and 30)
- ✓ ZF TE ML 07 F (SAE 30)

Meets the requirements of

- ✓ CATERPILLAR TO-4
- ✓ CATERPILLAR HYDO Advanced
- ✓ ALLISON TES 439
- ✓ KOMATSU Clutch test
- ✓ ZF TE ML 07D

Suitable for transmission systems

DANA, EATON-FULLER, ROCKWELL, JCB...

APPLICATIONS

TOTAL DYNATRANS ACX 10W, 30 & 50 are adapted to **hydraulic systems, Powershift gearboxes, axles** and **final drives** when the manufacturer recommends a fluid meeting one of the above mentioned specifications.

TOTAL DYNATRANS ACX is recommended for Mining, Earthmoving and Construction machinery between -20°C and +50°C :

- SAE 10W grade is mainly used in hydraulic systems
- SAE 30 grade is mainly used in Powershift gearboxes
- SAE 50 grade is mainly used in axles and final drives

For temperatures below -20°C, the use of DYNATRANS ACX 0W-20 is strongly advised.

TOTAL DYNATRANS ACX 10W and 30 should be used in replacement of **CATERPILLAR HYDO Advanced 10, 20 and 30**, with a drain interval extension up to 3000 working hours and more, within regular oil analysis.

PERFORMANCES AND CUSTOMER BENEFITS

- Excellent anti-wear and anticorrosion properties, increasing the durability of the lubricated organs
- Good performance with respect to elastomers, without aggressiveness to the pipes
- The 10W grade has a very fast de-aeration time and a good filterability, avoiding any cavitation risks in hydraulic pumps
- Friction properties adapted to the types of CATERPILLAR, KOMATSU and other machinery friction materials
- Very shear stable viscosities preserving the hydraulic pumps volumetric efficiency
- Very fluid at low temperatures, they are immediately active when starting by cold climate
- Formulated with selected base oils associated to a recently developed chemistry, they provide to the end user, a better oxidation resistance at high temperature together with a draining interval extension
- Emulsifying, they fully keep condensation water in emulsion and avoid any pump breaks in Winter or rapid degradation in Summer

PHYSICAL AND CHEMICAL CHARACTERISTICS*

TOTAL DYNATRANS ACX	Method	10W	30	50	
Kinematic Viscosity at 40°C	mm ² /s	ASTM D445	41	93	195
Kinematic Viscosity at 100°C	mm ² /s	ASTM D445	6.6	11.2	18.4
Viscosity Index	-	ASTM D2270	118	107	104
Pour Point	°C	ASTM D97	-36	-30	-21
Zinc content (min)	ppm	ICP	900	900	900
Oxidation stability	h	ASTM D943	> 5000	> 5000	

* The features mentioned above are average values obtained with some variability in production and do not constitute a specification.

TOTAL LUBRIFIANTS
562, avenue du Parc de l'Île
92029 Nanterre cedex
FRANCE

TOTAL DYNATRANS ACX 10W – 30 – 50

Update 06/2017

www.lubricants.total.com



This lubricant does not cause adverse health effects when used in the intended application.
A safety datasheet is accessible on request from your local dealer or on the website www.quickfds.com