



# Fluide CC

## Automatic transmissions and hydraulic systems

### PERFORMANCES LEVELS

#### OEM-Approved

- ✓ Mercedes-Benz MB-Approval 236.2

#### Meets the requirements

- ✓ GM Type A Suffix A
- ✓ MAN 339 Type A

### APPLICATIONS

Automatic transmissions and hydraulic systems for which the manufacturer recommends the use of an ATF type A suffix A (TASA) transmission fluid:

- automatic gear boxes.
- couplers and torque converters.
- power assisted steering assemblies

### CUSTOMER BENEFITS

- **Special friction properties** providing controlled slide of friction components: the quality of gear changing implies indeed a smooth clutching action without excessive slide and free from chatter.
- **Low temperature fluidity** to eliminate jerking and overloading of circuits when starting in very cold weather.
- **High anti-oxydant power, good thermal stability** and **detergent characteristics** designed to conserve properties of the lubricant over extensive periods of use and to avoid formation of gum and varnish deposits in the circuits

TOTAL LUBRIFIANTS – Immeuble Spazio  
562, avenue du Parc de l'île  
92029 Nanterre cedex  
France

FLUIDE CC  
Update: 07/2017



- Does not affect copper and seals.
- **High viscosity index** and **viscosity stability** in operation.
- **Anti-corrosion** and **anti-rust capacity** as well as **high anti-foaming capacity**.
- **Antiwear properties** (protection of gear tothing, thrust bearings and pumps).

## PHYSICAL AND CHEMICAL CHARACTERISTICS

FLUIDE CC	Unit	Method	Value
Colour	-	ASTM D1500	Red
Density at 15°C	kg/m <sup>3</sup>	ASTM D4052	880,9
Kinematic Viscosity at 40 °C	mm <sup>2</sup> /s	ASTM D445	39,19
Kinematic Viscosity at 100°C	mm <sup>2</sup> /s	ASTM D445	7,466
Brookfield Viscosity at -40°C	cP	ASTM D2983	34443
Viscosity Index	-	ASTM D2270	160
Pour Point	°C	ASTM D97	-51
Flash Point	°C	ASTM D92	200

*\*The features mentioned above are average values obtained with some variability in production and do not constitute a specification.*

## RECOMMENDATIONS FOR USE

Before using the product, it is important to check the service manual of the vehicle: the drain is carried out according to the manufacturer's requirements.

The product should not be stored at a temperature above 60 °C while avoiding exposure to strong sunlight, extreme cold or high temperature variations.

All packages should be protected from bad weather conditions. Otherwise, the drums should be stored horizontally to avoid a possible contamination by water and the damage of the product label.

TOTAL LUBRIFIANTS – Immeuble Spazio  
562, avenue du Parc de l'île  
92029 Nanterre cedex  
France

FLUIDE CC  
Update: 07/2017



*This lubricant does not cause adverse health effects when used in the intended application. A safety datasheet, is accessible on request from your local dealer.*

---

## **HEALTH, SAFETY AND ENVIRONMENT**

---

Based on available information, this product does not cause adverse health effects when used in the intended application and the recommendations provided in the Safety Data Sheet (MSDS) are followed. The information is accessible on request from your local dealer or on the website [www.quickfds.com](http://www.quickfds.com).

This product should not be used for applications other than those for which it is intended.

If disposing of used product, take care to protect the environment and comply with local regulations.