

# PNEUMA SY



*Pneumatic tools*



**Anti-freeze oil for pneumatic tools.**

## APPLICATIONS

### Pneumatic tools

- Percussion air tools, all sound proof pneumatic tools.
- Non miscible with conventionnal mineral oils.

## ADVANTAGES

### Long lasting equipment

- High impact strenght due to the extreme pressure additivation preventing the equipment wear.
- Water repellent.
- Antirust.

### Allows the soft running of the equipment

- Prevents the ice build up at air tool exhaust.
- Low pour point.

TYPICAL CHARACTERISTICS	METHODS	UNITS	PNEUMA SY
Density at 15°C	ISO 3675	kg/m <sup>3</sup>	1090
Kinematic viscosity at 40°C	ISO 3104	mm <sup>2</sup> /s	17
Kinematic viscosity at 0°C	ISO 3104	mm <sup>2</sup> /s	88
Pour point	ISO 3016	°C	< - 40
pH		-	8,2

Above characteristics are mean values given as an information.

**TOTAL LUBRIFIANTS**  
**Industrie & Spécialités**  
12-09-2011 (supersedes13-12-2002  
PNEUMA SY  
1/1



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.  
A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded from [www.quick-fds.com](http://www.quick-fds.com).